



CHEERWE TELECOM ALL RIGHTS RESERVED 2010

www.chinacheerwe.com E-mail:sales@chinacheerwe.com

Cold Applied In-Line Closures, Dome Ended Fiber Optic Joint Closure,
Fiber Optic Inline Butt Splice Closure

Item No.:CWFOC1006



They are typically used for customer drops, tap-offs (taut sheath) and in-line splice applications.

The wrap-around thermoplastic body consists of two hingeable shells that are sealed with an O-ring system and that can easily be closed using latches. One mass splicing tray and cable attachment units are provided at the inside.

Features

- In-line thermoplastic closure
- Four cable ports, two on each side
- Cable sealing based on gel technology (2 knobs for gel compression)
- Easy re-entry and re-closure
- Compatible with most cable constructions (loose tube, central core, slotted core)

- 4 general cable ports, could be suitable for connect different branch cable, including uncut cable.
- It is used high quality imported material to make sure the closure service life.
- It is used raw adhesive tape for sealing.
- It applies to direct buried, aerial, pipe-lined applications, and solves the storage problem

Dimension for the Closure (LxWxH)	390mmx210mmx120mm	
Ports For Cable Entrance	3 Ports each side	
Suitable Diameter For the Cable	Φ16 mm	
Max capacity	Bundle Cable	12-96
	Ribbon Cable	144
Quantity Of Splice Tray Installed	1-4	