



CHEERWE TELECOM ALL RIGHTS RESERVED 2010

www.chinacheerwe.com E-mail:sales@chinacheerwe.com

Wall Mounted and Direct Buried Fiber Optic Splice Closure

Item No.:CWFOC1005



They are typically used for customer drops, tap-offs (taut sheath) and in-line splice applications, Also be suitable For FTTH Installations.

The wrap-around thermoplastic body consists of two hingeable shells that are sealed with an O-ring system and that can easily be closed using latches. One mass splicing tray and cable attachment units are provided at the inside.

Features

- In-line thermoplastic closure
- Four cable ports, two on each side

- Cable sealing based on gel technology (2 knobs for gel compression)
- Easy re-entry and re-closure
- Compatible with most cable constructions (loose tube, central core, slotted core)
- 4 general cable ports, could be suitable for connect different branch cable, including uncut cable.
- It is used high quality imported material to make sure the closure service life.
- It is used raw adhesive tape for sealing.
- It applies to direct buried, aerial, pipe-lined applications, and solves the storage problem

Dimension for the Closure (L×W×H)		280mm×200mm×90mm
Ports For Cable Entrance		2 Ports
Suitable Diameter For the Cable		Φ14 mm
Max capacity	Bundle Cable	12-96
	Ribbon Cable	144
Quantity Of Splice Tray Installed		1-2

柱挂 Pole mounting 架空 Aerial 直埋 Direct buried 管道 Pipe-lined 壁挂 Wall-mounting

